



SAFETY DATA SHEET

Issuing Date: 22-Dec-2011

Revision Date: 27-Sep-2016

Revision Number: 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 03174YVP-1

Product Name: METAL PRETREATMENT WASH PRIMER, MIL-C-8514C, AMEND 1, PART A

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements
 Harmful if swallowed
 Causes skin irritation
 Causes serious eye damage
 May cause an allergic skin reaction
 May cause cancer
 May cause drowsiness or dizziness
 Highly flammable liquid and vapor

Appearance Opaque **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
ETHYL ALCOHOL	64-17-5	50% - 60%	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³
BUTYL ALCOHOL	71-36-3	10% - 20%	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³
ZINC TETRAOXYCHROMATE	49663-84-5	5% - 10%	N/A	TWA: 5 µg/m ³ Ceiling: 0.1 mg/m ³ CrO3 applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect
ISOPROPYL ALCOHOL	67-63-0	1% - 5%	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³
METHANOL	67-56-1	1% - 5%	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³

4. FIRST AID MEASURES

First Aid Measures

General advice	Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
Eye Contact	Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. Call a physician immediately. If symptoms persist, call a physician.
Skin Contact	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove to fresh air. If not breathing, give artificial respiration. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	No information available.
Indication of any immediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Flammable. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.
-----------------------------	--

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and flame.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
ETHYL ALCOHOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
BUTYL ALCOHOL 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
ZINC TETRAOXYCHROMATE 49663-84-5	N/A	TWA: 5 µg/m ³ Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m ³ Cr(VI) TWA: 0.0002 mg/m ³ Cr
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³

			STEL: 250 ppm STEL: 325 mg/m ³
--	--	--	--

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Appearance	Opaque
Odor	Solvent.	Odor Threshold	No data available
pH	No data available	Flash Point	52 °F / 11 °C
Decomposition temperature	No data available	Boiling Point	145 °F / 63 °C
Melting Point / Melting Range	No data available	Freezing Point	No data available
Vapor Pressure @20°C (kPa)	No data available	Partition coefficient:	No data available
Vapor Density	No data available	Density	No data available
Bulk density	No data available	Specific Gravity	0.89
Evaporation Rate	No data available	Water solubility	No data available
Dynamic viscosity	No data available	Weight per Gallon (lbs/gal):	7.37
		Flammability Limits in Air	
		Upper	14.04 %
		Lower	2.33 %

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability
Stable under recommended storage conditions.

Conditions to Avoid
Extremes of temperature and direct sunlight.

Incompatible Materials
None known based on information supplied.

Hazardous Decomposition Products
None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation There is no data for this product.
Eye Contact There is no data for this product.
Skin Contact There is no data for this product.
Ingestion There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ALCOHOL 64-17-5	7060 mg/kg (Rat)	N/A	124.7 mg/L (Rat) 4 h
BUTYL ALCOHOL 71-36-3	700 mg/kg (Rat)	3402 mg/kg (Rabbit)	8000 ppm (Rat) 4 h
ISOPROPYL ALCOHOL 67-63-0	1870 mg/kg (Rat)	4059 mg/kg (Rabbit)	72600 mg/m ³ (Rat) 4 h
METHANOL 67-56-1	6200 mg/kg (Rat)	N/A	22500 ppm (Rat) 8 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
MUTAGENIC EFFECTS No information available.
Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHYL ALCOHOL 64-17-5	A3	Group 1	Known	X
ZINC TETRAOXYCHROMATE 49663-84-5	N/A	Group 1	Known	X
ISOPROPYL ALCOHOL 67-63-0	N/A	Group 1 Group 3	N/A	X

Legend:
ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive Toxicity No information available.
Specific target organ systemic toxicity (single exposure) No information available.
Specific target organ systemic toxicity (repeated exposure) No information available.
Chronic Toxicity Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin. Repeated contact may cause allergic reactions in very susceptible persons.
Target Organ Effects Blood, Central nervous system (CNS), Eyes, Gastrointestinal tract (GI), Kidney, Liver, Lungs, Reproductive system, Respiratory system, Skin.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	1457 mg/kg
ATEmix (dermal)	6094 mg/kg
ATEmix (inhalation-dust/mist)	18.1 mg/l
Oral LD50	2701 mg/kg (rat) Estimated
Dermal LD50	6812 mg/kg (rat) Estimated
Inhalation LC50	226788 mg/l (mist) (dust) mg/m ³ Estimated
Inhalation LC50	ml/m ³ (vapor) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
ETHYL ALCOHOL 64-17-5	N/A	13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static
BUTYL ALCOHOL 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ISOPROPYL ALCOHOL 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	1400000: 96 h Lepomis macrochirus µg/L LC50 9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
METHANOL 67-56-1	N/A	100: 96 h Pimephales promelas mg/L LC50 static 28200: 96 h Pimephales promelas mg/L LC50 flow-through 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static	N/A

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
ETHYL ALCOHOL 64-17-5	-0.32
BUTYL ALCOHOL 71-36-3	0.785
ISOPROPYL ALCOHOL 67-63-0	0.05
METHANOL 67-56-1	-0.77

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
BUTYL ALCOHOL 71-36-3	Included in waste stream: F039	N/A
METHANOL 67-56-1	Included in waste stream: F039	N/A

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHYL ALCOHOL 64-17-5	Toxic Ignitable
BUTYL ALCOHOL 71-36-3	Toxic
ZINC TETRAOXYCHROMATE 49663-84-5	Toxic Corrosive Ignitable
ISOPROPYL ALCOHOL 67-63-0	Toxic Ignitable
METHANOL 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II, RQ
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

MEX

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II

Special Provisions A3, A72
Description UN1263, Paint, 3, II

IATA

UN-No UN1263
Hazard class 3
Packing Group II
ERG Code 3L
Special Provisions A3, A72, A192

IMDG/IMO

UN-No UN1263
Hazard class 3
Packing Group II
EmS-No F-E, S-E
Special Provisions 163, 367

RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Description UN1263, Paint, 3, II

ADR/RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640C, 650, 367
Description UN1263, Paint, 3, II, (D/E)
ADR/RID-Labels 3

ADN

Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II
Hazard Labels 3
Limited Quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
BUTYL ALCOHOL	71-36-3	1.0
ZINC TETRAOXYCHROMATE	49663-84-5	0.1 1.0
ISOPROPYL ALCOHOL	67-63-0	1.0
METHANOL	67-56-1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
ZINC TETRAOXYCHROMATE	49663-84-5	Present
METHANOL	67-56-1	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC TETRAOXYCHROMATE	N/A	X	N/A	N/A

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
BUTYL ALCOHOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHANOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
ETHYL ALCOHOL	64-17-5	Carcinogen Developmental
ZINC TETRAOXYCHROMATE	49663-84-5	Carcinogen Developmental

		Female Reproductive Male Reproductive
METHANOL	67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ETHYL ALCOHOL	X	X	X	X	X
BUTYL ALCOHOL	X	X	X	N/A	X
ZINC TETRAOXYCHROMATE	N/A	X	X	X	N/A
ISOPROPYL ALCOHOL	X	X	X	N/A	X
METHANOL	X	X	X	X	X

International Regulations


Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
ETHYL ALCOHOL	N/A	Mexico: TWA 1000 ppm Mexico: TWA 1900 mg/m ³
BUTYL ALCOHOL	N/A	Mexico: Ceiling 50 ppm Mexico: Ceiling 150 mg/m ³
ZINC TETRAOXYCHROMATE	A1	Mexico: TWA 0.01 mg/m ³ Mexico: TWA 0.5 mg/m ³
ISOPROPYL ALCOHOL	N/A	Mexico: TWA 400 ppm Mexico: TWA 980 mg/m ³ Mexico: STEL 500 ppm Mexico: STEL 1225 mg/m ³
METHANOL	N/A	Mexico: TWA 200 ppm Mexico: TWA 260 mg/m ³ Mexico: STEL 250 ppm Mexico: STEL 310 mg/m ³

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



HMIS Health Hazard 2 * Flammability 3 Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

* Chronic Health Hazard

Issuing Date: 22-Dec-2011
Revision Date: 27-Sep-2016
Revision Note
No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 03174YVP-1

end